

ANTODE DICTURE (BY NEW TODAY OF THE COMPANY OF THE

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office

BEST AVAILABLE COPY August 27, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/486,566

FILING DATE: *July 11, 2003*

RELATED PCT APPLICATION NUMBER: PCT/US04/22347

Certified by

Jon W Dudas

Acting Under Secretary of Commerce for Intellectual Property and Acting Director of the U.S. Patent and Trademark Office





PROVISIONAL APPLICATION FOR PATENT COVER SHEET This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53 (c).

Express Mail Label N	EV330680185US			

Given Name (first and middle [if any]) Zvika Rosenberg Mevaseret Zion, Israel Modiin, Israel Aviram Tam Additional Inventors are being named on the separately numbered sheets attached hereto TITLE OF THE INVENTION (500 characters max) True CD Direct all correspondence to: CORRESPONDENCE ADDRESS Customer Number OR Type Customer Number here Tarek N. Fahmi Blakely, Sokoloff, Taylor & Zafman LLP										
Ovadya Aviram Menadeva Tam Rishon Le Zion, Israel Rishon Le Zion, I										
Additional Inventors are being named on the separately numbered sheets attached hereto TITLE OF THE INVENTION (500 characters max) True CD Direct all correspondence to: CORRESPONDENCE ADDRESS Customer Number										
TITLE OF THE INVENTION (500 characters max) True CD Direct all correspondence to: CORRESPONDENCE ADDRESS Customer Number OR Type Customer Number here Tarek N. Fahmi Blakely, Sokoloff, Taylor & Zafman LLP										
TITLE OF THE INVENTION (500 characters max) True CD Direct all correspondence to: CORRESPONDENCE ADDRESS Customer Number OR Type Customer Number here Tarek N. Fahmi Blakely, Sokoloff, Taylor & Zafman LLP										
Direct all correspondence to: CORRESPONDENCE ADDRESS ☐ Customer Number										
Customer Number OR Type Customer Number here *08791* Tarek N. Fahmi Blakely, Sokoloff, Taylor & Zafman LLP	True CD									
OR Type Customer Number here *08791* Tarek N. Fahmi Blakely, Sokoloff, Taylor & Zafman LLP	RESS (1911) AND									
Tarek N. Fahmi Blakely, Sokoloff, Taylor & Zafman LLP										
Individual Name Blakely, Sokoloff, Taylor & Zafman LLP	Type Customer Number nere									
Address 12400 Wilshire Boulevard, Seventh Floor										
Address										
City Los Angeles State California ZIP 90025-103	ZIP 90025-1030									
Country USA Telephone (408) 947-8200 Fax (408) 947-	Fax (408) 947-8280									
ENCLOSED APPLICATION PARTS (check all that apply)										
Specification Number of Pages 8 CD(s), Number										
Drawing(s) Number of Sheets Other (specify)										
Application Data Sheet. See 37 CFR 1.76										
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)										
Applicant claims small entity status. See 37 CFR 1.27. FILING FEE AMOUNT (\$)										
A check or money order is enclosed to cover the filing fees The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number: Payment by credit card. Form PTO-2038 is attached.										
The Invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.										
No Yes, the name of the U.S. Government agency and the Government contract number are:										
Respectfully submitted, / Date 7/11/2003										
TYPED or PRINTED NAME Tarek N. Fahmi REGISTRATION NO. 41,402										
TELEPHONE (408) 947-8200 Docket Number: 6317P070										

UNITED STATES PROVISIONAL PATENT APPLICATION

For

TRUE CD

Inventors:

Zvika Rosenberg. Mevaseret Zion, Israel Ovadya Menadeva, Modiin, Israel Aviram Tam, Rishon Le Zion, Israel

Prepared by:

APPLIED MATERIALS ISRAEL, LTD.
Legal Department
P.O. Box 450A
Santa Clara, California 95050

Attorney's Docket No.: 8604 USA L/PDC/CD-SEM/OR

True CD

Problem definition

[0001] Classical CD metrology using Top-Down SEM scanning (top view) measurements gives satisfactory accuracy and matching relative to other techniques (AFM, Cross Sections, OCD) in general. However, when the specimen edge width (from top-down scanning) is the same order of magnitude or smaller then the Beam-Print (see figure 1), this measurement become less reliable and less sensitive to changes (see figures 2 and 3).




Figure 1: Beam-Print - The edge width (EW) as measured on the waveform generated by scanning a 90 deg slope




Figure 2: The Edge-Width (EW) is insensitive to changes of actual edge projection (EP)




Figure 3: Small edge width may exist due to steep slope (EW2) or small height (EW2).

[0002] This phenomenon is caused by the self-occlusion of the specimen bottom when viewing from the top view or by the fact that the SEM signal reflects the electron beam print rather then the actual edge-width. The bottom detection deteriorates when the sidewall become steeper. Until, there is no signal from the bottom of the edge in negative sidewall slopes.

[0003] Few methods were suggested to overcome this problem mainly by using only the tilted views of the CD measurement. These methods suffer from the symmetry assumption that can lead to a measurement error from one side.

When symmetry is not assumed it requires many scanning/exposures of the features that can effect the feature size measurement and require longer measurement time (shrinkage, charging, etc.).

[0004] We suggest to use the information from the tilted views for CD measurement combined with marking a reference Point/Line over the wafer in order to overcome this problem.

[0005] In the framework of this approach, the Bottom CD values are calculated as result of the CD Marking points and the visible bottom point taken from two tilted views. This method allows improving the CD measurement accuracy for steep edges without assuming symmetry or the need of more than two scans of the feature.

[0006] The advantage of the proposed method that it is independent of the feature height and does not requires more than two scanning of the feature.

Strategy

[0007] Option 1. When true CD is required, we suggest to use the true CD measurement scheme as described in Figure 4.




Figure 4: True CD Measurement Scheme details

The True CD scheme

[0008] This scheme combines the two tilt views, and the marking step; one view from each side. Here we do not assume that the height is given, since the measurement point lay on the level. The bottom CD can be easily calculated from the two tilts measurements. In addition we do not assume that the line is symmetric since we measurement is done from the two sidewalls.

[0009] The reference Marking (ML) can be done using the SEM scanning or alternatively trough a FIB device. The shape of the marking element can be point, Line, array of lines or any other feature/features that can be viewed and measured by the SEM.




Figure 5: CD = D2-D1

GI ssary

[0010] IR is the scanned image from the Right tilt see example in figure 6
[0011] IL is the scanned image from the Left tilt see example in figure 7
[0012] ML is the marked reference point, Line, Array of lines.
[0013] CD is the bottom measurement of the given feature
[0014] D1 is the measured distance between the visible bottom and ML in IL
[0015] D2 is the measured distance between the visible bottom and ML in IR

Example of IL: Left tilt scan image IL simulation




Figure 6

Example of IR: Right tilt scan image IR simulation




Figure 7

Option 2. Conditional target concept as follows:

[0016] We can use the preliminary scanning measurements to determine whether True CD scheme (Option 1) is required. Top-Down measurements are performed for low-slope edges and Tilted measurements are performed for steep edges. Note that the preliminary scanning may be performed in scan conditions different then the actual conditions of the final measurement (exposure, pixel size, etc.) or in the vicinity of the actual measured region (e.g. further up the measured line).

[0017] This condition can be determined by several methods. We describe these methods on the Conditions A, B, C, D and no condition at all.

Condition A - DIN

[0018] In this method we store a set of reference images that represent the state of the steep sidewall lines. Then using a distance function we decide whether the condition fulfill if the value is above some threshold. In the case that this condition fulfill we continue to Option 1. This distance function can be implement using the conventional Discrete Inspection methods such as correlation function, absolute distance,...

Condition B – CD limit

[0019] In this method we determine a limit both upper & lower on the bottom CD measurement value. Whenever the measurement exceeds this limit then the condition is fulfilled and we continue to Option 1.

Condition C - Edge-width

[0020] In this method we determine a lower limit on the edge-width measurement value. Whenever the measured edge width is smaller than this limit, the condition is fulfilled and we continue to Option 1.

C ndition D - Function Fit

[0021] In this method we fit a family of functions to the waveform signal and we determine a limit both upper & lower on the fitted function parameters value. When ever the parameters exceed limit then the condition fulfill and we continue to Option 1. This family of functions can be any common mathematical function such as polynomials, exponentials, etc.

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US04/022347

International filing date:

12 July 2004 (12.07.2004)

Document type:

Certified copy of priority document

Document details:

Country/Office: US

Number:

60/486,566

Filing date:

11 July 2003 (11.07.2003)

Date of receipt at the International Bureau: 06 September 2004 (06.09.2004)

Remark: Priority document submitted or transmitted to the International Bureau in

compliance with Rule 17.1(a) or (b)



This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

BLACK BORDERS

IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

FADED TEXT OR DRAWING

BLURRED OR ILLEGIBLE TEXT OR DRAWING

SKEWED/SLANTED IMAGES

COLOR OR BLACK AND WHITE PHOTOGRAPHS

GRAY SCALE DOCUMENTS

LINES OR MARKS ON ORIGINAL DOCUMENT

REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

☐ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.